

**COMTAC XS** 











- Slim cup design
- Active-volume function in stereo
- Last setting is stored when switched off
- Fully independent dual earphone system for active volume and external radio signal, for maximum security
- An external radio signal has priority and will function even when the ComTac is switched off or out of power
- Automatically switches off after two hours if no function is used. Two signals are emitted as a warning that the ComTac will switch off in one minute if no function is activated
- Battery life is about 250 hours. Three warning signals are emitted every 30 seconds for five minutes when power is low, then the headset switches off
- Audio input jack to allow connection to an external radio
- Available as headset.

MT15H69FB-02 378

Description	Product code	Attachment	Weight (g)
Standard	MT15H69FB-02 378	Foldable headband	295
Headset J11	MT15H69FB-38 378	Foldable headband	315
Standard	MT15H69FB-08 378SV	Foldable headband	295
Headset J11	MT15H69FB-38 378SV	Foldable headband	315

**Colour**

**MT15H69FB-\*\* \*\*\***

Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	14.4	17.4	24.1	31.1	31.5	38.1	37.3
Standard Deviation (dB)	4.8	3.4	3	2.2	3	2.8	3.2
Assumed Protection (dB)	9.6	14	21.1	28.9	28.5	35.3	34.1

SNR=26 H=31 M=24 L=16